

**SPECIFICATIONS**

Old-world country charm paired with deep gray to black tones and a natural sparkle.

**THIN VENEER**

LENGTH	2" - 10" Irregular
HEIGHT	2" - 10" Irregular
THICKNESS	¾" - 1 ½"
YIELD	10-15 lbs/ft²

**ASTM C-97 – ABSORPTION & BULK SPECIFIC GRAVITY**

WATER ABSORPTION	.14%
BULK SPECIFIC GRAVITY	2.78

**ASTM C-170 – COMPRESSIVE STRENGTH**

PARALLEL TO RIFT DRY	22,230 psi
PARALLEL TO RIFT, WET	14,610 psi
PERPENDICULAR TO RIFT, DRY	23,510 psi
PERPENDICULAR TO RIFT, WET	14,040 psi

**ASTM C-99 – MODULUS OF RUPTURE**

PARALLEL TO RIFT DRY	2,040 psi
PARALLEL TO RIFT, WET	1,700 psi
PERPENDICULAR TO RIFT, DRY	4,070 psi
PERPENDICULAR TO RIFT, WET	1,700 psi

**ASTM C-880 – FLEXURAL STRENGTH**

PARALLEL TO RIFT DRY	1,640 psi
PARALLEL TO RIFT, WET	1,260 psi
PERPENDICULAR TO RIFT, DRY	2,840 psi
PERPENDICULAR TO RIFT, WET	2,440 psi

