

STARLIGHT BLACK GRANITE DIMENSIONAL DRYSTACK

SPECIFICATIONS

Deep natural black granite in a contemporary, linear style with little to no joint exposed.

THIN VENEER

LENGTH	4" - 30" Random
HEIGHT*	Sawn 2", 4", & 6"
THICKNESS	3/4" - 1 1/2"
YIELD	10-15 lbs/ft ²

*Typical height ratio: 20% = 2", 50% = 4", 30% = 6". Additional heights available upon request.

ASTM C-97 – ABSORPTION & BULK SPECIFIC GRAVITY

WATER ABSORPTION	.06%
BULK SPECIFIC GRAVITY	2.885

ASTM C-170 – COMPRESSIVE STRENGTH

PARALLEL TO RIFT DRY	22,450 psi
PARALLEL TO RIFT, WET	20,390 psi
PERPENDICULAR TO RIFT, DRY	24,000 psi
PERPENDICULAR TO RIFT, WET	15,860 psi

ASTM C-99 – MODULUS OF RUPTURE

PARALLEL TO RIFT DRY	2,380 psi
PARALLEL TO RIFT, WET	2,570 psi
PERPENDICULAR TO RIFT, DRY	2,280 psi
PERPENDICULAR TO RIFT, WET	2,110 psi

ASTM C-880 – FLEXURAL STRENGTH

PARALLEL TO RIFT DRY	2,060 psi
PARALLEL TO RIFT, WET	2,280 psi
PERPENDICULAR TO RIFT, DRY	1,990 psi
PERPENDICULAR TO RIFT, WET	1,940 psi

