

8" SAWN CUT DRYWALL SIERRA

SPECIFICATIONS

LENGTH	8" - 40" Random
HEIGHT	6" or 7" Sawn
DEPTH	7½" - 8½"
YIELD	15-20 sq. ft. per ton
CONTENT	Granite
ORIGIN	North America



ASTM C-97 – ABSORPTION & BULK SPECIFIC GRAVITY

WATER ABSORPTION	.16%
BULK SPECIFIC GRAVITY	2.691

ASTM C-170 – COMPRESSIVE STRENGTH

PARALLEL TO RIFT DRY	31,250 psi
PARALLEL TO RIFT, WET	17,640 psi
PERPENDICULAR TO RIFT, DRY	27,190 psi
PERPENDICULAR TO RIFT, WET	19,710 psi

ASTM C-99 – MODULUS OF RUPTURE

PARALLEL TO RIFT DRY	1,860 psi
PARALLEL TO RIFT, WET	1,050 psi
PERPENDICULAR TO RIFT, DRY	2,910 psi
PERPENDICULAR TO RIFT, WET	1,680 psi

ASTM C-880 – FLEXURAL STRENGTH

PARALLEL TO RIFT DRY	3,960 psi
PARALLEL TO RIFT, WET	2,080 psi
PERPENDICULAR TO RIFT, DRY	3,030 psi
PERPENDICULAR TO RIFT, WET	1,770 psi

Kafka Granite's Natural Stone Sawn Cut Drywall is sure to add sophistication and elegance to dry stacked walls in your outdoor spaces. Each stone is sawn on the top and bottom to simplify installation and give a clean look, while both faces and ends are split to allow for a more natural appearance. Kafka Granite Sawn Cut Drywall will give your backyard or commercial project a profound presence.

