

4" SAWN EDGING IMPERIAL GRAY

SPECIFICATIONS

| | |
|---------|-----------------------------|
| LENGTH | 8" – 24" Random |
| HEIGHT | 4" Sawn |
| DEPTH | 3½" - 4½" Random |
| YIELD | 90 – 110 linear ft. per ton |
| CONTENT | Granite |
| ORIGIN | North America |



Blending seamlessly with our other Natural Stone Hardscapes, Kafka Granite's Sawn Edging is available in four natural stone colors. Sawn to consistent 4" heights, the product marries a convenient installation with the sophistication of natural stone. Kafka's Sawn Edging adds a thoughtful and impressive detail to any landscape project.

ASTM C-97 – ABSORPTION & BULK SPECIFIC GRAVITY

| | |
|-----------------------|-------|
| WATER ABSORPTION | .09% |
| BULK SPECIFIC GRAVITY | 2.672 |

ASTM C-170 – COMPRESSIVE STRENGTH

| | |
|----------------------------|------------|
| PARALLEL TO RIFT DRY | 34,280 psi |
| PARALLEL TO RIFT, WET | 29,460 psi |
| PERPENDICULAR TO RIFT, DRY | 32,750 psi |
| PERPENDICULAR TO RIFT, WET | 31,770 psi |

ASTM C-99 – MODULUS OF RUPTURE

| | |
|----------------------------|-----------|
| PARALLEL TO RIFT DRY | 2,410 psi |
| PARALLEL TO RIFT, WET | 1,910 psi |
| PERPENDICULAR TO RIFT, DRY | 2,540 psi |
| PERPENDICULAR TO RIFT, WET | 2,060 psi |

ASTM C-880 – FLEXURAL STRENGTH

| | |
|----------------------------|-----------|
| PARALLEL TO RIFT DRY | 2,440 psi |
| PARALLEL TO RIFT, WET | 2,150 psi |
| PERPENDICULAR TO RIFT, DRY | 2,510 psi |
| PERPENDICULAR TO RIFT, WET | 2,050 psi |

