

# THERMAL-TOP STEPS HARVEST GOLD

## SPECIFICATIONS

LENGTH	36" or 48" Sawn
DEPTH/RUN	18" or 24" Sawn
HEIGHT/RISE	6" or 7" Sawn
FINISH	Thermal Top, Rockfaced on Three Sides
CONTENT	Quartzitic Sandstone
ORIGIN	North America



### ASTM C-97 – ABSORPTION & BULK SPECIFIC GRAVITY

WATER ABSORPTION	.78%
BULK SPECIFIC GRAVITY	2.489

### ASTM C-170 – COMPRESSIVE STRENGTH

PARALLEL TO RIFT DRY	31,890 psi
PARALLEL TO RIFT, WET	20,950 psi
PERPENDICULAR TO RIFT, DRY	30,860 psi
PERPENDICULAR TO RIFT, WET	29,970 psi

### ASTM C-99 – MODULUS OF RUPTURE

PARALLEL TO RIFT DRY	2,000 psi
PARALLEL TO RIFT, WET	1,980 psi
PERPENDICULAR TO RIFT, DRY	1,910 psi
PERPENDICULAR TO RIFT, WET	1,520 psi

### ASTM C-880 – FLEXURAL STRENGTH

PARALLEL TO RIFT DRY	2,160 psi
PARALLEL TO RIFT, WET	1,820 psi
PERPENDICULAR TO RIFT, DRY	1,760 psi
PERPENDICULAR TO RIFT, WET	1,690 psi

*Kafka Granite's Natural Stone Thermal-Top Steps provide an impressive display to your landscaping. Each step is sawn to height to provide an efficient installation, which eliminates shimming and re-leveling. These steps are also rockfaced on one long side and two short sides to showcase the unique character of the natural stone. Each step has a thermal top finish to provide added traction for a non-skid surface. Kafka Granite Thermal-Top Steps are sure to deliver a lifetime of durability and beauty to your residential or commercial project.*

