

# THERMAL-TOP STEPS STARLIGHT BLACK

## SPECIFICATIONS

LENGTH	36" or 48" Sawn
DEPTH/RUN	18" or 24" Sawn
HEIGHT/RISE	6" or 7" Sawn
FINISH	Thermal Top, Rockfaced on Three Sides
CONTENT	Granite
ORIGIN	North America



### ASTM C-97 – ABSORPTION & BULK SPECIFIC GRAVITY

WATER ABSORPTION	.06%
BULK SPECIFIC GRAVITY	2.885

### ASTM C-170 – COMPRESSIVE STRENGTH

PARALLEL TO RIFT DRY	22,450 psi
PARALLEL TO RIFT, WET	20,390 psi
PERPENDICULAR TO RIFT, DRY	24,000 psi
PERPENDICULAR TO RIFT, WET	15,860 psi

### ASTM C-99 – MODULUS OF RUPTURE

PARALLEL TO RIFT DRY	2,380 psi
PARALLEL TO RIFT, WET	2,570 psi
PERPENDICULAR TO RIFT, DRY	2,280 psi
PERPENDICULAR TO RIFT, WET	2,110 psi

### ASTM C-880 – FLEXURAL STRENGTH

PARALLEL TO RIFT DRY	2,060 psi
PARALLEL TO RIFT, WET	2,280 psi
PERPENDICULAR TO RIFT, DRY	1,990 psi
PERPENDICULAR TO RIFT, WET	1,940 psi

*Kafka Granite's Natural Stone Thermal-Top Steps provide an impressive display to your landscaping. Each step is sawn to height to provide an efficient installation, which eliminates shimming and re-leveling. These steps are also rockfaced on one long side and two short sides to showcase the unique character of the natural stone. Each step has a thermal top finish to provide added traction for a non-skid surface. Kafka Granite Thermal-Top Steps are sure to deliver a lifetime of durability and beauty to your residential or commercial project.*

