

SPECIFICATIONS

LENGTH	Per Order
WIDTH	Per Order
THICKNESS	Standard 2¼" or 3", or Per Order
FINISH	Sawn
CONTENT	Granite
ORIGIN	North America



Round out your landscape project with the addition of Kafka's Treads, Caps, and Coping. These natural stone elements are available in four classic Kafka colors and are custom produced to fit your project. Each natural stone color takes on a new life with the various finishing options available. Add texture and traction with a Thermal or Bush Hammer finish, or opt for a Sawn or Honed finish to create clean lines and a contemporary flair.

ASTM C-97 – ABSORPTION & BULK SPECIFIC GRAVITY

WATER ABSORPTION	.16%
BULK SPECIFIC GRAVITY	2.691

ASTM C-170 – COMPRESSIVE STRENGTH

PARALLEL TO RIFT DRY	31,250 psi
PARALLEL TO RIFT, WET	17,640 psi
PERPENDICULAR TO RIFT, DRY	27,190 psi
PERPENDICULAR TO RIFT, WET	19,710 psi

ASTM C-99 – MODULUS OF RUPTURE

PARALLEL TO RIFT DRY	1,860 psi
PARALLEL TO RIFT, WET	1,050 psi
PERPENDICULAR TO RIFT, DRY	2,910 psi
PERPENDICULAR TO RIFT, WET	1,680 psi

ASTM C-880 – FLEXURAL STRENGTH

PARALLEL TO RIFT DRY	3,960 psi
PARALLEL TO RIFT, WET	2,080 psi
PERPENDICULAR TO RIFT, DRY	3,030 psi
PERPENDICULAR TO RIFT, WET	1,770 psi

