

8" SAWN CUT DRYWALL HARVEST GOLD

SPECIFICATIONS

LENGTH	8" - 40" Random
HEIGHT	6" or 4" Sawn
DEPTH	7½" - 8½"
YIELD	15-20 sq. ft. per ton
CONTENT	Quartzitic Sandstone
ORIGIN	North America



ASTM C-97 – ABSORPTION & BULK SPECIFIC GRAVITY

WATER ABSORPTION	.78%
BULK SPECIFIC GRAVITY	2.489

ASTM C-170 – COMPRESSIVE STRENGTH

PARALLEL TO RIFT DRY	31,890 psi
PARALLEL TO RIFT, WET	20,950 psi
PERPENDICULAR TO RIFT, DRY	30,860 psi
PERPENDICULAR TO RIFT, WET	29,970 psi

ASTM C-99 – MODULUS OF RUPTURE

PARALLEL TO RIFT DRY	2,000 psi
PARALLEL TO RIFT, WET	1,980 psi
PERPENDICULAR TO RIFT, DRY	1,910 psi
PERPENDICULAR TO RIFT, WET	1,520 psi

ASTM C-880 – FLEXURAL STRENGTH

PARALLEL TO RIFT DRY	2,160 psi
PARALLEL TO RIFT, WET	1,820 psi
PERPENDICULAR TO RIFT, DRY	1,760 psi
PERPENDICULAR TO RIFT, WET	1,690 psi

Kafka Granite's Natural Stone Sawn Cut Drywall is sure to add sophistication and elegance to dry stacked walls in your outdoor spaces. Each stone is sawn on the top and bottom to simplify installation and give a clean look, while both faces and ends are split to allow for a more natural appearance. Kafka Granite Sawn Cut Drywall will give your backyard or commercial project a profound presence.

