

8" SAWN CUT DRYWALL IMPERIAL GRAY

SPECIFICATIONS

LENGTH	8" - 40" Random
HEIGHT	6" or 4" Sawn
DEPTH	7½" - 8½"
YIELD	15-20 sq. ft. per ton
CONTENT	Granite
ORIGIN	North America



ASTM C-97 – ABSORPTION & BULK SPECIFIC GRAVITY

WATER ABSORPTION	.09%
BULK SPECIFIC GRAVITY	2.672

ASTM C-170 – COMPRESSIVE STRENGTH

PARALLEL TO RIFT DRY	34,280 psi
PARALLEL TO RIFT, WET	29,460 psi
PERPENDICULAR TO RIFT, DRY	32,750 psi
PERPENDICULAR TO RIFT, WET	31,770 psi

ASTM C-99 – MODULUS OF RUPTURE

PARALLEL TO RIFT DRY	2,410 psi
PARALLEL TO RIFT, WET	1,910 psi
PERPENDICULAR TO RIFT, DRY	2,540 psi
PERPENDICULAR TO RIFT, WET	2,060 psi

ASTM C-880 – FLEXURAL STRENGTH

PARALLEL TO RIFT DRY	2,440 psi
PARALLEL TO RIFT, WET	2,150 psi
PERPENDICULAR TO RIFT, DRY	2,510 psi
PERPENDICULAR TO RIFT, WET	2,050 psi

Kafka Granite's Natural Stone Sawn Cut Drywall is sure to add sophistication and elegance to dry stacked walls in your outdoor spaces. Each stone is sawn on the top and bottom to simplify installation and give a clean look, while both faces and ends are split to allow for a more natural appearance. Kafka Granite Sawn Cut Drywall will give your backyard or commercial project a profound presence.

