

## SPECIFICATIONS

Refined gray marble with white accents in a sophisticated look.

### THIN VENEER

LENGTH	4" - 30" Random (12" Average)
HEIGHT	4" - 12" Random
THICKNESS	¾" - 1 ½"
YIELD	10-15 lbs/ft²

### ASTM C-97 – ABSORPTION & BULK SPECIFIC GRAVITY

WATER ABSORPTION	.10%
BULK SPECIFIC GRAVITY	2.906

### ASTM C-170 – COMPRESSIVE STRENGTH

PARALLEL TO RIFT DRY	21,493 psi
PARALLEL TO RIFT, WET	21,626 psi
PERPENDICULAR TO RIFT, DRY	19,688 psi
PERPENDICULAR TO RIFT, WET	13,472 psi

### ASTM C-99 – MODULUS OF RUPTURE

PARALLEL TO RIFT DRY	2,081 psi
PARALLEL TO RIFT, WET	1,855 psi
PERPENDICULAR TO RIFT, DRY	2,189 psi
PERPENDICULAR TO RIFT, WET	1,825 psi

### ASTM C-880 – FLEXURAL STRENGTH

PARALLEL TO RIFT DRY	2,300 psi
PARALLEL TO RIFT, WET	2,110 psi
PERPENDICULAR TO RIFT, DRY	1,249 psi
PERPENDICULAR TO RIFT, WET	1,683 psi

