4" SAWN EDGING IMPERIAL GRAY

SPECIFICATIONS

LENGTH 8" – 24" Random

HEIGHT 4" Sawn

DEPTH 3½" - 4½" Random

YIELD 90 – 110 linear ft. per ton

CONTENT Granite

ORIGIN North America



WATER ABSORPTION .09%
BULK SPECIFIC GRAVITY 2.672

ASTM C-170 - COMPRESSIVE STRENGTH

PARALLEL TO RIFT DRY 34,280 psi
PARALLEL TO RIFT, WET 29,460 psi
PERPENDICULAR TO RIFT, DRY 32,750 psi
PERPENDICULAR TO RIFT, WET 31,770 psi

ASTM C-99 - MODULUS OF RUPTURE

PARALLEL TO RIFT DRY 2,410 psi
PARALLEL TO RIFT, WET 1,910 psi
PERPENDICULAR TO RIFT, DRY 2,540 psi
PERPENDICULAR TO RIFT, WET 2,060 psi

ASTM C-880 - FLEXURAL STRENGTH

PARALLEL TO RIFT DRY
2,440 psi
PARALLEL TO RIFT, WET
2,150 psi
PERPENDICULAR TO RIFT, DRY
2,510 psi
PERPENDICULAR TO RIFT, WET
2,050 psi



Blending seamlessly with our other Natural Stone Hardscapes, Kafka Granite's Sawn Edging is available in four natural stone colors. Sawn to consistent 4" heights, the product marries a convenient installation with the sophistication of natural stone. Kafka's Sawn Edging adds a thoughtful and impressive detail to any landscape project.



