

SPECIFICATIONS

LENGTH	12" – 48" Random
DEPTH	3½"
THICKNESS	2¼"
FINISH	Sawn
CONTENT	Granite
ORIGIN	North America



Kafka's natural stone Silles deliver a premium, finished look and complement other Kafka natural stone products. Each natural stone color takes on a new life with the various finishing options available: Thermal, Bush Hammer, Sawn, or Honed.

ASTM C-97 – ABSORPTION & BULK SPECIFIC GRAVITY

WATER ABSORPTION	.06%
BULK SPECIFIC GRAVITY	2.885

ASTM C-170 – COMPRESSIVE STRENGTH

PARALLEL TO RIFT DRY	22,450 psi
PARALLEL TO RIFT, WET	20,390 psi
PERPENDICULAR TO RIFT, DRY	24,000 psi
PERPENDICULAR TO RIFT, WET	15,860 psi

ASTM C-99 – MODULUS OF RUPTURE

PARALLEL TO RIFT DRY	2,380 psi
PARALLEL TO RIFT, WET	2,570 psi
PERPENDICULAR TO RIFT, DRY	2,280 psi
PERPENDICULAR TO RIFT, WET	2,110 psi

ASTM C-880 – FLEXURAL STRENGTH

PARALLEL TO RIFT DRY	2,060 psi
PARALLEL TO RIFT, WET	2,280 psi
PERPENDICULAR TO RIFT, DRY	1,990 psi
PERPENDICULAR TO RIFT, WET	1,940 psi

