

# STARLIGHT BLACK GRANITE SAWN DIMENSIONAL

## SPECIFICATIONS

An ultra-contemporary sawn black granite with subtle white veining and a smooth, clean finish.

### THIN VENEER

LENGTH	Sawn 4" - 30" Random (12" Average)
HEIGHT	Sawn 5"
THICKNESS	¾" - 1 ¼"
YIELD	10-15 lbs/ft²

### ASTM C-97 – ABSORPTION & BULK SPECIFIC GRAVITY

WATER ABSORPTION	.06%
BULK SPECIFIC GRAVITY	2.885

### ASTM C-170 – COMPRESSIVE STRENGTH

PARALLEL TO RIFT DRY	22,450 psi
PARALLEL TO RIFT, WET	20,390 psi
PERPENDICULAR TO RIFT, DRY	24,000 psi
PERPENDICULAR TO RIFT, WET	15,860 psi

### ASTM C-99 – MODULUS OF RUPTURE

PARALLEL TO RIFT DRY	2,380 psi
PARALLEL TO RIFT, WET	2,570 psi
PERPENDICULAR TO RIFT, DRY	2,280 psi
PERPENDICULAR TO RIFT, WET	2,110 psi

### ASTM C-880 – FLEXURAL STRENGTH

PARALLEL TO RIFT DRY	2,060 psi
PARALLEL TO RIFT, WET	2,280 psi
PERPENDICULAR TO RIFT, DRY	1,990 psi
PERPENDICULAR TO RIFT, WET	1,940 psi

