TREADS, CAPS & COPING HARVEST GOLD

SPECIFICATIONS

LENGTH Per Order

WIDTH Per Order

THICKNESS 2½"

FINISH Sawn

CONTENT Quartzitic Sandstone

ORIGIN North America

ASTM C-97 - ABSORPTION & BULK SPECIFIC GRAVITY

WATER ABSORPTION .78%
BULK SPECIFIC GRAVITY 2.489

ASTM C-170 - COMPRESSIVE STRENGTH

PARALLEL TO RIFT DRY 31,890 psi
PARALLEL TO RIFT, WET 20,950 psi
PERPENDICULAR TO RIFT, DRY 30,860 psi
PERPENDICULAR TO RIFT, WET 29,970 psi

ASTM C-99 - MODULUS OF RUPTURE

PARALLEL TO RIFT DRY 2,000 psi
PARALLEL TO RIFT, WET 1,980 psi
PERPENDICULAR TO RIFT, DRY 1,910 psi
PERPENDICULAR TO RIFT, WET 1,520 psi

ASTM C-880 - FLEXURAL STRENGTH

PARALLEL TO RIFT DRY 2,160 psi
PARALLEL TO RIFT, WET 1,820 psi
PERPENDICULAR TO RIFT, DRY 1,760 psi
PERPENDICULAR TO RIFT, WET 1,690 psi



Round out your landscape project with the addition of Kafka's Treads, Caps, and Coping. These natural stone elements are available in four classic Kafka colors and are custom produced to fit your project. Each natural stone color takes on a new life with the various finishing options available. Add texture and traction with a Thermal or Bush Hammer finish, or opt for a Sawn or Honed finish to create clean lines and a contemporary flair.

