

American Engineering Testing, Inc. Wausau | Green Bay

4203 Schofield Ave, Ste 1 Schofield, WI 54476 (715) 359-3534

3194 Market St., Ste C Green Bay, WI 54304 (920) 347-1286

Issue No: 1

Toll Free: (800) 972-6364

www.amengtest.com Report No: MAT:16-07878-S19

Material Test Report

Client: KAFKA GRANITE, LLC

CC: Jeremy Bores John Meyer

Project: 2016 CONSTRUCTION PROJECTS

This document shall not be reproduced, except in full. without written approval from American Engineering Testing, Inc.

Date of Issue: Reviewed By:

7/29/2016 Paul Michlig, CET Construction Manager

Sample Details

Job No:

Sample ID 16-07878-S19

Field Sample ID 19 **Date Sampled** 7/12/2016 Source Kafka Granite Material Sunset Pink Granite

Specification None

12-02155

Sampling Method Sampled by Client Location Kafka Granite **Date Submitted** 7/13/2016

Test Results Description Method Result Limits Specific Gravity (OD) ASTM C 127 2.59 Specific Gravity (SSD) 2.61 Apparent Specific Gravity 2.64 Absorption (%) 0.6 Density Determined Without First Drying? No **Additional Notes Date Tested** 7/19/2016

Comments

N/A



July 29, 2016

CONSULTANTS

ENVIRONMENTAL

GEOTECHNICAL

MATERIALS

FORENSICS

Mr. Jeremy Bores Kafka Granite, LLC 550 East Highway 153 Mosinee, WI 54455

Re: Mohs Hardness Testing 2016 Construction Projects Schofield, WI AET Project No. 12-02155

Mr. Bores:

This report presents the results of our Mohs hardness testing of one sample of stone submitted by you on July 20, 2016. The stone is to be referred to as "#19 Sunset Pink Granite". Four stones were submitted to our laboratory and one was chosen for testing. The scope of our work in this report was confined to performing Mohs hardness testing on one stone sample.

Conclusions

Based on our observations and analysis our opinions are as follows:

- 1. The overall hardness of the "#19 Sunset Pink Granite" stone is approximately 7 to 7.5 on the Mohs scale. The number is based upon testing values of the overall hardness of the rock using Mohs hardness picks.
- 2. The stone appeared to generally consist of a medium grained, igneous rock. A hardness value determination of the stone based upon the mineral assemblage was not conducted. Mohs picks with hardness 3 thru 8 were used on the stone. The Mohs hardness picks determined an approximate overall hardness of 7 to 7.5. This hardness is a more consistent result then using the mineral assemblage because the Mohs hardness picks were drawn directly across a freshly lapped surface of the stone.
- 3. In general, rocks are not homogeneous with regards to Mohs mineral hardness. The best effort was made to accomplish the hardness analysis at a representative area within the stone selected. Because rocks can consist of several different minerals with different quantities and different hardness, and the Mohs scale represents the hardness of individual minerals, the Mohs scale should only be used as an approximation when determining the overall hardness of a rock.

Mr. Jeremy Bores Sample ID: #19 Sunset Pink Granite AET Project No. 12-02155 July 29, 2016 Page 2 of 2

Procedures

Our work was performed on July 26, 2016 and subsequent dates. The hardness testing was completed through the use of standard geologic Mohs hardness points and optical microscopy on a lapped hand sample. The review was performed in general accordance with Standard Operating Procedure 24-LAB-004, "Petrographic Examination of Aggregates for Concrete, ASTM C295." Observations were made using an Olympus SZX-12 stereo-zoom binocular microscope with magnification up to 160x.

Photographs are included to illustrate our work and conclusions.

Remarks

The sample will be retained for a period of at least sixty days from the date of this report. Unless further instructions are received by that time, the sample may be discarded. The geologic services for this project have been conducted in a manner consistent with that level of care and skill exercised by members of the profession currently practicing in this area under similar budget and time constraints. The results relate only to the sample analyzed. No warranty, express or implied, is made.

It has been a pleasure to serve you on this project. Should you have any questions on this report, please do not hesitate to call.

Respectfully,

American Engineering Testing, Inc.

Christopher J. Braaten, PG Petrographer/Geologist MN License #48312 Phone: 651-659-1352

cbraaten@amengtest.com

Attachment: "Materials Test Report"

Reviewed by:

American Engineering Testing, Inc.

Gerard Moulzolf, PG

Vice President/Principal Retrographer

MN License #30023


Phone: 651-659-1346

gmoulzolf@amengtest.com

12-02155 **DATE:** July 29, 2016

Scholfield, WI

2016 Construction Projects



РНОТО: 1

PROJECT:

SAMPLE ID:

#19 Sunset Pink Granite

DESCRIPTION:

Overall view of the sample as received.



SAMPLE ID:

#19 Sunset Pink Granite

DESCRIPTION:

View of the stone selected for hardness testing.

AET PROJECT NO: 12-02155 **DATE:** July 29, 2016 **PROJECT:**

2016 Construction Projects

Scholfield, WI



РНОТО: 3

SAMPLE ID: MAG:

#19 Sunset Pink Granite 5x

DESCRIPTION:

View of the lapped cross section of the stone.

РНОТО: 4



SAMPLE ID: MAG:

#19 Sunset Pink Granite 5x

DESCRIPTION: View of the lapped cross section of the stone after Mohs hardness testing. Note that hardness picks 3 thru 6 did not scratch, hardness pick 7 scratched a few minerals, and hardness pick 8 scratched all minerals. The general Mohs hardness would be approximately 7 to 7.5.