

# IRREGULAR THERMAL FLAGSTONE HARVEST GOLD

## SPECIFICATIONS

LENGTH	18" - 48" Irregular
WIDTH	18" - 48" Irregular
THICKNESS	Sawn 1 <sup>3</sup> / <sub>4</sub> " - 2 <sup>1</sup> / <sub>4</sub> " Random
FINISH	Thermal Top
YIELD	65 - 80 sq. ft. per ton
CONTENT	Quartzitic Sandstone
ORIGIN	North America



### ASTM C-97 – ABSORPTION & BULK SPECIFIC GRAVITY

WATER ABSORPTION	.78%
BULK SPECIFIC GRAVITY	2.489

### ASTM C-170 – COMPRESSIVE STRENGTH

PARALLEL TO RIFT DRY	31,890 psi
PARALLEL TO RIFT, WET	20,950 psi
PERPENDICULAR TO RIFT, DRY	30,860 psi
PERPENDICULAR TO RIFT, WET	29,970 psi

### ASTM C-99 – MODULUS OF RUPTURE

PARALLEL TO RIFT DRY	2,000 psi
PARALLEL TO RIFT, WET	1,980 psi
PERPENDICULAR TO RIFT, DRY	1,910 psi
PERPENDICULAR TO RIFT, WET	1,520 psi

### ASTM C-880 – FLEXURAL STRENGTH

PARALLEL TO RIFT DRY	2,160 psi
PARALLEL TO RIFT, WET	1,820 psi
PERPENDICULAR TO RIFT, DRY	1,760 psi
PERPENDICULAR TO RIFT, WET	1,690 psi

*Kafka Granite's Thermal Flagstone provides a premium natural stone alternative to manufactured hardscapes. Each stone has a sawn height with a 1/2" tolerance, which cuts down on sorting and installation time, and virtually eliminates shimming and re-leveling. The top surface has a thermal finish to provide traction and accentuate the unique character of the natural stone. Kafka Granite Thermal Flagstone is the perfect option for a sophisticated look in your hardscape project.*

