

# MISTY GRAY MARBLE DRYSTACK

## SPECIFICATIONS

A contemporary light gray marble sawn to a linear style with little to no joint exposed.

### THIN VENEER

LENGTH	4" - 30" Random (12" Average)
HEIGHT*	Sawn 2", 4", & 6"
THICKNESS	3/4" - 1 1/2"
YIELD	10-15 lbs/ft <sup>2</sup>

\*Typical height ratio: 20% = 2", 50% = 4", 30% = 6". Additional heights available upon request.

### ASTM C-97 – ABSORPTION & BULK SPECIFIC GRAVITY

WATER ABSORPTION	.10%
BULK SPECIFIC GRAVITY	2.906

### ASTM C-170 – COMPRESSIVE STRENGTH

PARALLEL TO RIFT DRY	21,493 psi
PARALLEL TO RIFT, WET	21,626 psi
PERPENDICULAR TO RIFT, DRY	19,688 psi
PERPENDICULAR TO RIFT, WET	13,472 psi

### ASTM C-99 – MODULUS OF RUPTURE

PARALLEL TO RIFT DRY	2,081 psi
PARALLEL TO RIFT, WET	1,855 psi
PERPENDICULAR TO RIFT, DRY	2,189 psi
PERPENDICULAR TO RIFT, WET	1,825 psi

### ASTM C-880 – FLEXURAL STRENGTH

PARALLEL TO RIFT DRY	2,300 psi
PARALLEL TO RIFT, WET	2,110 psi
PERPENDICULAR TO RIFT, DRY	1,249 psi
PERPENDICULAR TO RIFT, WET	1,683 psi

